



Portable Generators

TSURUMI PUMP x POWERED BY HONDA

TPG

TPG TSURUMI PUMP x POWERED BY HONDA Portable Generators

- **TSURUMI TPG-series portable generators** are designed to withstand the severe conditions of construction jobsites or industrial applications, especially where extra durability and dependable, stable power are required. Ideal to supply the power to Tsurumi's single-phase submersible pumps and all your electrical power tools such as drills, saws, lighting and heaters due to AVR system.
- **Powered by Made in Japan Honda OHV engine** for efficient fuel and oil consumption with oil alert system to shut off motor if oil falls below safe operation level.
- **Large Air Filter** for superior emission control.
- **Large, Silent Muffler** to greatly reduce noise.
- **Rubber Vibration Pads** isolate generator/engine set for maximum protection and noise reduction.
- **High Capacity Fuel Tank with Fuel Gauge** for extended run-time.
- **Volt Meter, Pilot Lamp and DC 12V Outlet** are equipped as standard.
- **Electric Starter** makes free from extra work for start-up.



Electric Starter available for TPG- 6000/ 7000HEL only

Standard Accessories

- AC 16A European Type Plug 2pcs.
- DC 12V Plug w/Cord & Clip 1pc.
- Hexagon Wrench 1pc.



Wheel kit available as option

Standard Specifications 50Hz

Model	TPG-3000HM	TPG-4000HM	TPG-6000HM	TPG-6000HEL	TPG-7000HM	TPG-7000HEL	
Engine	Engine Brand						HONDA
	Engine Model						GX160 GX240 GX340 GX390
	Displacement (cm ³)						163 242 337 389
	Max. Output (kW / 4000rpm)						4.0 5.9 8.1 9.6
	Type						Air Cooled, 4-cycle, OHV Gasoline Engine
	Oil Alert System						Standard
	Ignition System						Transfer (C.D.I.)
Generator	Electric Start						N/A Standard N/A Standard
	Alternator						Self-exciting, 2-pole, Field Rotating Type, Single-phase
	Voltage Regulator						AVR
	Phase						Single
	AC Max. Output (kVA)						2.2 3.6 4.8 5.5
	AC Rated Output (kVA)						2.0 3.0 4.0 5.0
	Rated Voltage						220V / 50Hz
Other Features	AC Outlet						16A European Type (Receptacle)×2
	DC Outlet						12V-8.3A (Receptacle)×1
	Pilot Lamp						Standard
	Volt Meter						Standard
Measurement	Fuel Tank Capacity (ℓ)						16.0 25.0
	Continuous Operating Hours (hr: 100% Load)						14.1 15.1 10.1 9.0
	Sound Level (dB(A) / 7m)						71 73 75 75 76 76
Measurement	Dimensions (mm / L×W×H)						595×414×495 685×534×509
	Dry Weight (kgs)						45.8 69.5 78.2 81.2 82.0 85.0

We reserve the right to change the specifications and designs for improvement without prior notice.

TSURUMI
MANUFACTURING CO., LTD.

Your Dealer